

Top Hammers

Eurodrill



RH 1X

RH 2X

RH 3X

RH 4X

RH 5X

RH 10X



HD RD


20 15

20 15

20 40

20

Drive		hydraulic	hydraulic	hydraulic	hydraulic	hydraulic	hydraulic
Weight	kg	80	95	165	200	350	410
Torque max.	daNm	106	212	250	500	550	1'100
Speed max.	rpm	292	364	270	360	212	214
Frequency	rpm	3'000	3'000 4'000	2'500 4'500	2'500 4'500	2'500 2'400	2'500
Impact energy / power	Nm (KW)	180	180	320	320	320	320
Oil requirement	l/min P	75@200bar	75@200bar	115@200bar	140@200bar	190@200bar	220@200bar
Conversion to rotary actuator X-series possible				Yes	Yes	Yes	Yes
Shaft	Typ R	32 / 38	32 / 38 / 51	32 / 38 / 51	32 / 38 / 51 / 76	32 / 38 / 51 / 76	32 / 38 / 51 / 76 / 114
Situated for drill feed	Typ	91 / 92	91 / 92	92	92	(92)	(92)
Recommended generators	Typ	KSD 93 F	KSD 93 F	KSD 93 F	(KSD 93 F)		



EURODRILL is a hydraulically operated high-performance drive for high demands.



X-Factor - flexible options with the same basic gearbox

ROTATING FLOATING SPINDLE BEATING

1 Grundgetriebe
3 Optionen

Option 1
Rotating drive

Option 2
Rotary drive with floating spindle

Option 3
Drive percussive