

IMP E

Injection mix pump



Specifications



Max delivery rate	ℓ/min	63
Pump pressure max.	bar	60
Grain size max.	mm	2
Pump type		● EP
Adjustable quantity		optional
Drive		Euro 16 A
Electrical connection		6.4; 7.7 KW / 400V
Drive		
Mixer mode		continuous mixer
Mixer content	ℓ	75
Mixer performance	m ³ /h	2
Buffer tank content	ℓ	150
Transport length	mm	1'200
Length	mm	1'590
Width	mm	795
Height	mm	1'310
Weight	kg	286

Available with

Remote control		on request
Cable control		on request
Link to Gerlogg		on request
Water meter		optional
Water tank		optional
Silo compatible		
Agitator in buffer tank		
Stepless		optional

Gear motor	4.2 kW – 242 Upm	5.5 kW – 406 Upm	5.5KW + FU 100 – 406 Upm
Gear	Spur gear	Spur gear	Spur gear
Electrical connection	16 A/ 5-polig	16 A/ 5-polig	16 A/ 5-polig
Generator	mind. 15 kVA	mind. 20 kVA	mind. 18 kVA

Flow rate & Pressure

K MUNG pump part 3 blue < 60 bar	14.0 ℓ/min	24.0 ℓ/min	6 – 24 ℓ/min
K MUNG pump part 8 orange < 50 bar	24.0 ℓ/min	39.0 ℓ/min	9 – 39 ℓ/min
K MUNG pump part 10 grey < 40 bar	39.0 ℓ/min	63.0 ℓ/min	15 – 63 ℓ/min



● Eccentric screw pump EP



Electric drive